



TECHNICAL INFORMATION

SUPRALIN S Eco Liq. Anticreasing Agent

It is a non-foaming oil based anticreasing agent for wet processes of blends with synthetic fibers, wool, silk and other fibers

- It decreases fiber-fiber and fiber-metal friction in every stage of textile process.
- Improves the lubricity of the material
- Especially effective on lycra and sensual fabrics
- Easy to dissolve in water

PROPERTIES

Appearance	yellowish transparent liquid
Ionic Character	Anionic
Ph	6.0-8.0
Solubility	Soluble in water at any ratio

APPLICATION

Supralin S Eco liq is used in all types of cellulosic fibers and blends, as well as in knitting, knitting, optical bleaching, dyeing and finishing processes of woven or knitted parts made of wool and silk.

Supralin S Eco Liq is always put into the bath first, that is, before other chemicals and dyes, because the fractures occur in the first minutes of the wet process.

The amount to be used depends on the material and the machine.
1-4% Supralin S Eco liq.

The product can be added directly to the float without pre-dilution..

PRECAUTIONS

Storage: The storage life in original package at 0-40 °C is 12 months.

Paints, pigments, and most of the chemicals are patented by Sozal Ltd or its subsidiaries in various industrial countries. The information and recommendations presented here have been created with great care, but they may not include every possible situation. These information and recommendations are non-binding guidelines and must be adapted to the conditions in force. Moreover, no liability is accepted for the non-written application areas and methods. Information and protective measures that are required to be specified can be obtained from the Safety Data Sheet