



## TECHNICAL INFORMATION

### SEGAFIX T24-C Liq.

#### Fixing Agent for Reactive Dyes

Segafix T24-C Liq. is a highly effective fixing agent for dyeing and prints with reactive dyes which imparts excellent wash fastness properties.

- Suitable for printing and dyeing with reactive dyes
- Washing, water and perspiration fastness developer
- Light Fastness: minimal influence on the light fastness and the shade of the dyeing.
- Formaldehyde free.
- Color and touch the minimum negative impact

## PROPERTIES

<b>Chemical Structure</b>	Polyamine copolymer
<b>Appearance</b>	Yellowish liquid
<b>Ionic character</b>	Cationic
<b>pH (1% sol.)</b>	6.0-8.0
<b>Solubility</b>	Easily soluble in water at any ratio

## Application

Segafix T24-C Liq. can be used in both the puller and padding method.

### Recommended washing and fixation process:

Dyeing and printing → Cold wash → Hot wash (50-60 °C) → Boiling wash( Segacel TBS 2g/L, 95-98 °C 10 min.)  
→ Cold wash → Fixation → Cold wash → Drying

- The most suitable usage amount depends on the desired depth of color and fastness.

### Exhaust

%0,5-1,5 Segafix T24-C Liq.

pH: 5-6

50 °C 20-30'

### Continue

5-15 g/L Segafix T24-C Liq.

pH: 5-6

**Storage:** The storage life in original package at 0-40 °C is 12 months.

Paints, pigments, and most of the chemicals are patented by Sozal Ltd or its subsidiaries in various industrial countries. The information and recommendations presented here have been created with great care, but they may not include every possible situation. These information and recommendations are non-binding guidelines and must be adapted to the conditions in force. Moreover, no liability is accepted for the non-written application areas and methods. Information and protective measures that are required to be specified can be obtained from the Safety Data Sheet.