



## TECHNICAL INFORMATION

### SEGACLEAR ARD

#### Organic, high performance reducing agent

- Segaclear ARD is used reduced bleaching process as a reducing agent.
- Cleaning of dyeing machines process can be used.
- Disperse dyeing and printing post-washing is used for reductive purposes.
- Segaclear ARD is also used instead of sodium hydrosulphite.

## PROPERTIES

<b>Component</b>	Thioureadioxide
<b>Appearance</b>	White powder
<b>Ionic character</b>	Anionic
<b>Compatibility</b>	Good for anionic and nonionic products not compatible with cationic products
<b>Solubility</b>	Soluble with water in any proportion.

## Application

### Free reductant

2g/L NaOH 48 °Be

2g/L Hydrosulphite

Treat for 20 min at 70–95 °C

### With Segaclear ARD

2–7 g/L Segaclear ARD

2–4 g/L NaOH 48 °Be

Treat for 20–30 min at 70–95 °C

## Precautions

### Safe Use and Handling

Good hygienic and industrial practices should be followed and, when employed as recommended, Segaclear ARD will not present any hazard. However, prolonged skin contact with the neat product should be avoided and any splashes on the skin should be washed off with water.

**Storage:** 12 month under 0°C –40°C in original packaging.

Paints, pigments, and most of the chemicals are patented by Sozal Ltd or its subsidiaries in various industrial countries. The information and recommendations presented here have been created with great care, but they may not include every possible situation. These information and recommendations are non-binding guidelines and must be adapted to the conditions in force. Moreover, no liability is accepted for the nonwritten application areas and methods. Information and protective measures that are required to be specified can be obtained from the Safety Data Sheet