



## TECHNICAL DATA SÖZALPRINT THICKENER 420

- It is a nonionic vinyl acrylic copolymer emulsion that does not contain APEO and formaldehyde.

### FEATURES

Physical Appearance	White liquid
pH	2.0-4.0
Ionic Structure	Nonionic
Density	Approx. 1.0 g/cm3

### SCOPE OF APPLICATION

- Sözalprint Thickener 420 is used for wood & paper adhesive and textile lamination.
- It can be diluted in all proportions with water before use. The film is transparent, medium hardness, and colorless.

### STORAGE

In order to protect against microorganisms, dispersion contains some initial protective agents.

However, under long storage conditions, a suitable preservative is used to further prevent microbial contamination. agent can be added. Necessary checks should be made regarding the effect and suitability of this preservative. During shipment,

The tank and pipes must be clean enough.

It can be stored for 12 months in closed barrels and drums in environments with temperatures between 5 and 35°C. Of the product

After the amount desired to be used is taken to maintain its homogeneity, the mouth of the container should be tightly closed.

Protect against freezing.

Most of the paints, pigments and chemicals are patented by Sözal Ltd or its subsidiaries in various industrial countries. The information and advice presented here is a great created with care, but they may not include every possible situation. This information and recommendations are non-binding and It needs to be adapted to the conditions.